


# Managing Fire & Smoke Barriers In Today's Healthcare Environment

Presented By: Kelly Mason  
Director of Healthcare Partnerships  
Specified Technologies Inc.




# Many Types of Applications


Cable Management



Mechanical, Electrical,  
Plumbing




Curtain Wall




Construction Joints




# In the world above the ceiling tiles... Out of sight can be out of mind!








# Even when new!





# U.L. Tested Rubber Matt?




# Even when we have made the effort...

Openings that once were sealed may no longer be.





# Scab Patches...Compliant?







# Giant Red Flag!





# UL Systems?????



# The UL System Must Meet the Application

- Rating of the barrier
- Proper barrier construction
- Proper penetrating item
- Annular space requirements

**More Than Just Red Caulk!!!**






# U.L. Systems

System No. W-L-1049



ANSI/UL1479 (ASTM E814)	CAN/ULC S115
F Ratings - 1 and 2 Hr (See Item 1)	F Rating - 1 and 2 Hr (See Item 1)
T Rating - 0 Hr	FT Rating - 0 Hr
L Rating At Ambient - Less Than 1 CFM/sq ft	FH Rating - 1 and 2 Hr (See Item 1)
L Rating At 400 F - Less Than 1 CFM/sq ft	FTH Rating - 0 Hr
	L Rating At Ambient - Less Than 1 CFM/sq ft
	L Rating At 400 F - Less Than 1 CFM/sq ft



1. **Wall Assembly** - The 1 or 2 hr fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner described in the individual U300 or U400 Series Wall or Partition Design in the UL Fire Resistance Directory and shall include the following construction features:
  - A. **Studs** - Wall framing may consist of either wood studs or steel channel studs. Wood studs to consist of nom 2 by 4 in. (51 by 102 mm) lumber spaced 16 in. (406 mm) OC. Steel studs to be min 3-5/8 3-1/2 in. (89 mm) wide and spaced max 24 in. (610 mm) OC. When steel studs are used and the diam of opening exceeds the width of stud cavity, the opening shall be framed on all sides using lengths of steel stud installed between the vertical studs and screw-attached to the steel studs at each end. The framed opening in the wall shall be 4 to 6 in. (102 to 152 mm) wider and 4 to 6 in. (102 to 152 mm) higher than the diam of the penetrating item such that, when the penetrating item is installed in the opening, a 2 to 3 in. (51 to 76 mm) clearance is present between the penetrating item and the framing on all four sides.
  - B. **Gypsum Board** - 5/8 in. (16 mm) thick, 4 ft (1.22 m) wide with square or tapered edges. The gypsum board type, thickness, number of layers, fastener type and sheet orientation shall be as specified in the individual U300 or U400 Series Design in the UL Fire Resistance Directory. Max diam of opening is 26 in. (660 mm) for steel stud walls. Max diam of opening is 14-1/2 in. (368 mm) for wood stud walls.  
 The hourly F and FH Ratings of the firestop system are equal to the hourly fire rating of the wall assembly in which it is installed.
- 1A. **Metallic Sleeve** - (Optional, Not Shown) - Cylindrical sleeve fabricated from min 0.016 in. (0.41 mm) to max 0.105 in. (2.7 mm) thick sheet steel. Length of steel sleeve to be equal to the thickness of wall. Longitudinal seam of sleeve welded or overlapped min 1 in. (25 mm). The ends of the steel sleeve shall be flush or recessed max 1/4 in. (6 mm) from wall surfaces.



**Specified Technologies Inc. 210 Evans Way Somerville, NJ 08876**

Reproduced courtesy of Underwriters Laboratories, Inc.  
Created or Revised: December 20, 2013



(800)992-1180 • (908)526-8000 • FAX (908)231-8415 • E-Mail:techserv@stifirestop.com • Website:www.stifirestop.com



W-L-1049  
PAGE 1 OF 2



# The UL Design Has Parameters



**System No. W-L-1049**



ANSI/UL1479 (ASTM E814)	CAN/ULC S115
F Ratings - 1 and 2 Hr (See Item 1)	F Rating - 1 and 2 Hr (See Item 1)
T Rating - 0 Hr	FT Rating - 0 Hr
L Rating At Ambient - Less Than 1 CFM/sq ft	FH Rating - 1 and 2 Hr (See Item 1)
L Rating At 400 F - Less Than 1 CFM/sq ft	FTH Rating - 0 Hr
	L Rating At Ambient - Less Than 1 CFM/sq ft
	L Rating At 400 F - Less Than 1 CFM/sq ft





# U.L. System Details

1. **Wall Assembly** - The 1 or 2 hr fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner described in the individual U300 or U400 Series Wall or Partition Design in the UL Fire Resistance Directory and shall include the following construction features:
  - A. **Studs** - Wall framing may consist of either wood studs or steel channel studs. Wood studs to consist of nom 2 by 4 in. (51 by 102 mm) lumber spaced 16 in. (406 mm) OC. Steel studs to be min 3-5/8 3-1/2 in. (89 mm) wide and spaced max 24 in. (610 mm) OC. When steel studs are used and the diam of opening exceeds the width of stud cavity, the opening shall be framed on all sides using lengths of steel stud installed between the vertical studs and screw-attached to the steel studs at each end. The framed opening in the wall shall be 4 to 6 in. (102 to 152 mm) wider and 4 to 6 in. (102 to 152 mm) higher than the diam of the penetrating item such that, when the penetrating item is installed in the opening, a 2 to 3 in. (51 to 76 mm) clearance is present between the penetrating item and the framing on all four sides.
  - B. **Gypsum Board\*** - 5/8 in. (16 mm) thick, 4 ft (1.22 m) wide with square or tapered edges. The gypsum board type, thickness, number of layers, fastener type and sheet orientation shall be as specified in the individual U300 or U400 Series Design in the UL Fire Resistance Directory. Max diam of opening is 26 in. (660 mm) for steel stud walls. Max diam of opening is 14-1/2 in. (368 mm) for wood stud walls.

**The hourly F and FH Ratings of the firestop system are equal to the hourly fire rating of the wall assembly in which it is installed.**
- 1A. **Metallic Sleeve** - (Optional, Not Shown) - Cylindrical sleeve fabricated from min 0.016 in. (0.41 mm) to max 0.105 in. (2.7 mm) thick sheet steel. Length of steel sleeve to be equal to the thickness of wall. Longitudinal seam of sleeve welded or overlapped min 1 in. (25 mm). The ends of the steel sleeve shall be flush or recessed max 1/4 in. (6 mm) from wall surfaces.



# System Details

2. **Through Penetrant** - One metallic pipe, conduit or tubing to be installed either concentrically or eccentrically within the firestop system. Pipe, conduit or tubing may be installed at an angle not greater than 45 degrees from perpendicular. The annular space between pipe, conduit or tubing and periphery of opening shall be min 0 in. (0 mm, point contact) to max 2 in. (51 mm). For maximum 16 in. (406 mm) diam (or smaller) pipes, annular space shall be min 0 in. (0 mm, point contact) to max 2 in. (51 mm). Pipe, conduit or tubing to be rigidly supported on both sides of wall assembly. The following types and sizes of metallic pipes, conduits or tubing may be used:
  - A. **Steel Pipe** - Nom 36 in. (914 mm) diam (or smaller) Schedule 10 (or heavier) steel pipe.
  - B. **Iron Pipe** - Nom 36 in. (914 mm) diam (or smaller) cast or ductile iron pipe.
  - C. **Conduit** - Nom 4 in. (102 mm) diam (or smaller) steel electrical metallic tubing, nom 6 in. (152 mm) diam (or smaller) steel conduit or nom 1 in. (25 mm) diam (or smaller) flexible steel conduit.
  - D. **Copper Tubing** - Nom 6 in. (152 mm) diam (or smaller) Type L (or heavier) copper tubing.
  - E. **Copper Pipe** - Nom 6 in. (152 mm) diam (or smaller) Regular (or heavier) copper pipe.
3. **Fill, Void or Cavity Material\* - Sealant** - Min 5/8 in. (16 mm) thickness of fill material applied within annulus, flush with both surfaces of wall. At the point contact location between through penetrant and gypsum board, a min 3/8 in. (10 mm) diam bead of fill material shall be applied at the gypsum board/through penetrant interface on both surfaces of wall.

**SPECIFIED TECHNOLOGIES INC** - SpecSeal Series SSS Sealant or SpecSeal LCI Sealant

\* Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.





# Seems Easy Enough! Competent Installations Require Understanding:


1. The role of barriers/compartimentation
2. How barriers are compromised
3. Following a UL system approach
4. Understanding basic product installation



# Standard Operating Practice

- A full overview as to what is expected of anyone working in a rated barrier
- A part of the bid documents
- Procedural requirements
- Performance requirements
- Submittal requirements
- Installation requirements

***Failure of any vendor to meet your SOC will result in contract termination***



# Make Expectations Clear!

- Because firestop installations in this facility are surveyed for strict adherence to code requirements, and to insure compliance, submittals, evidence of formal training for the installer, and destructive inspections of completed work are required. It is the responsibility, therefore, of the vendor to understand the requirements herein, provide all labor, training, materials, and equipment necessary to meet these requirements.
- Due to the critical nature of these life-safety systems, failure to provide firestop installations in compliance with this SOP is cause for contract termination.








## MasterFormat® 2004 Edition

- [General Firestopping \(07 84 00\)](#)
- [Section Penetration Firestopping \(07 84 13\)](#)
- [Joint Systems \(07 84 43\)](#)
- [Building Perimeter Firestopping \(07 84 53\)](#)
- [Division 22 Specification – Plumbing Firestopping](#)
- [Division 23 Specification – HVAC Firestopping](#)
- [Division 26 Specification – Electrical Specification](#)
- [Division 27 Specification – Communications Firestopping](#)
- [Canadian General Firestopping \(07 84 00\)](#)



## Specification Review Services

Did you know that many specifications for firestopping reference older fire test standards or obsolete products? Let our firestop experts assist by reviewing your firestop specifications and making appropriate recommendations. STI provides this service free of charge.



# Procedural Requirements For Personnel Entering Barriers

- Obtain S.O.P.
- Obtain prints detailing rated construction
- Obtain manufactures application guide
- Achieve certification for installers (FIT-I)
- Prepare itemized schedule of penetrations
- Select U.L. systems that meet the applications
- Submit in a formal submittal format



# Submittal Of U.L. Assemblies

- UL Tested Systems: Submit drawings showing typical installation details for the methods of installation.
- Indicate which firestop materials will be used and requirements for different hourly ratings.
- Submit manufacturer's product literature for each type of firestop material to be installed. Literature shall indicate product characteristics, typical uses, performance and limitation criteria, and test data.
- Approved Applicator: Submit documents to demonstrate capability to perform intended work. (FIT Certification)





# Combine UL System Coverage With Complete Product Solutions....

- Outline A Customized System Matrix For The Facility.

## SCHEDULE OF REQUIRED UL FIRESTOP SYSTEMS

**NOTE TO INSTALLERS: Only The Following UL Classified Firestop Systems Shall Be Accepted In This Facility**

MECHANICAL PENETRATIONS	Sleeved	Insulated	Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Bare Metallic	No	No	SSS Sealant	CAJ-1079	CAJ-1079	WL-1049
Bare Metallic	Yes	No	SSS Sealant	CAJ-1217	CAJ-1217	WL-1079
Fiberglass Insulated Pipe	Optional	Yes	SSS Sealant	CAJ-5087	CAJ-5087	WL-5014
AB/PVC Foam Insulated Pipe	No	Yes	SSS Sealant	CAJ-5133	CAJ-5133	WL-5054
Multiple Metallic	No	No	SSS Sealant			WL-1168
Multiple Metallic	Yes	No	SSS Sealant			WL-1127
Multiple Mixed	No	Optional	SSS Sealant	CAJ-8053	CAJ-8053	WL-8003
Multiple Mixed Pipe	No	No	SSS Sealant	CAJ-8093	CAJ-8093	
Fire Retardant Poly Propylene Pipe	No	No	SSS/SSCollars	CAJ-2045	CAJ-2045	WL-2029
Fire Retardant Poly Propylene Pipe	Optional	No	Wrap Strip Tuok Im	FA-2077	WJ-2020	WL-2048
All Plastics 1.5"-6" (Collar Device Only)	No	No	SSS/SSCollars	CAJ-2125	CAJ-2125	WL-2074
ELECTRICAL PENETRATIONS	Sleeved	Re-Enterable	Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Single Conduit	No	No	SSS Sealant	CAJ-1079	CAJ-1079	WL-1049
Multiple Metallic	No	No	SSS Sealant			WL-1093
Multiple Metallic	No	No	SSS Sealant			WL-1168
Multiple Mixed Conduits and Tubing	No	Yes	Pillows	CAJ-8093	CAJ-8093	
Multiple Metallic	No	No	SSS Sealant	CAJ-8053	CAJ-8053	WL-8003
Flush-mounted electrical and VDV outlet boxes		No	Putty Pads			CLV
COM/DATA PENETRATIONS	Sleeved	Re-Enterable	Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Single Cable Bundle	No	Yes	Single EZ-Paths	CAJ-3214	C-AJ-3214 or WJ-3099	WL-3219
Multiple Cable Bundles	No	Yes	Ganged EZ-Paths	F-A-3015	WJ-3098	WL-3218
Center hung cable tray	No	Yes	Pillows		WJ-4021	WL-4029
Open ladder cable tray	No	Yes	Pillows	CAJ-4029	CAJ-4029	WL-4008
Single Innerduct	Optional	No	SSS Sealant	CAJ-2140	CAJ-2140	WL-2093
Multiple Innerduct	Yes	Yes	Pillows		WJ-2054	WL-2178
GROUPED PENETRATIONS IN EXISTING BARRIERS	Sleeved	Re-Enterable	Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Multiple Mixed		Yes	Pillows	CAJ-8093	CAJ-8093	
Multiple Mixed		No	SSS Sealant	CAJ-8113	CAJ-8113	
Multiple Mixed		No	SSM Mortar	CAJ-8114	CAJ-8114	
Multiple Mixed		No	SSM Mortar	CAJ-8115	CAJ-8115	
HVAC PENETRATIONS	Sleeved	Re-Enterable	Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Non-Dampened Rectangular duct	No		SSS Sealant		WJ-7007	WL-7025
Non-Dampened Flat oval duct	No		SSS Sealant		WJ-7013	WL-7033
Non-Dampened Spiral duct	No		SSS Sealant		WJ-7005	WL-7026
Non-Dampened Insulated duct	No		SSS/SSW		WJ-7011	WL-7028
SHAFT WALLS			Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Metallic Pipe - Sealed from one side			SSS Sealant			WL-1251
PVC Pipe - Sealed from one side			SSS Sealant			WL-2257
Cable Bundle - Sealed from one side			SSS Sealant			WL-3179
Round Non-Dampened HVAC - Sealed from one side			SSS Sealant			WL-3090
Rectangular Non-Dampened HVAC - Sealed from one side			SSS Sealant			WL-3090
Head of Wall			ES Sealant			HWD-0184
ARCHITECTURAL JOINTS & BLANK OPENINGS			Product(s)	Concrete Floor	Concrete Wall	GWB Wall
Walls to Flat Concrete Deck			ES Sealant		HWD-1006	HWD-0079
Walls to Flat Concrete Deck			AS Spray		HWD-1005	HWD-0044
Walls to Fluted Metal Deck			ES Sealant		HWD-0339	HWD-0034
Walls to Fluted Metal Deck			AS Spray		HWD-0088	HWD-0043
Walls to Fluted Metal Deck, Fireproofing, I-Beams			AS Spray		HWD-0140	HWD-0099
Gypsum Walls to Fluted Metal Deck, Castle Cut			ES Sealant			HWD-0153
Wall to Wall Joint			ES Sealant	WWD-0004		
Perimeter Joint, Gyp. Sheathed Stud Wall, Vision Glass			AS Spray	CWS-1002		
Perimeter Joint, Spandrel Glass, Vision Glass			AS Spray	CWS-2003		
Floor to Floor Joint			ES Sealant	FFD-1008		
Blank Openings			SSS Sealant	CAJ-0014	CAJ-0014	
Blank Openings			Pillows	CAJ-0061	CAJ-0061	WL-0010
PERIMETER FIRE CONTAINMENT SYSTEMS			Product(s)	System		
3 Hour Spandrel Glass			AS Spray	CW-S-2049		
3 Hour Concrete			AS Spray	CW-S-2048		




**FIRESTOP**  
SPECIFIED TECHNOLOGIES INC.



# BMP: Standardized System Base

## Documentation





# Penetration Permit Form

- This permit will be given with a designated start. Determined by the facility
- Will allow access above the ceiling
- Will be displayed at all times

**bmp**  
barrier management program

**RESTRICTED SPACE ACCESS PERMIT**

Location: \_\_\_\_\_ Date: \_\_\_\_\_ Time: \_\_\_\_\_

Permit Type:  Certain  Expected

Vendor/Contractor  Staff

Work to be performed: \_\_\_\_\_

**FOR OFFICIAL USE ONLY DO NOT WRITE BELOW THIS LINE**

Applicant Has Current Firestop Installer's Training Certificate?  
 Applicant Has Current Hot Work Certificate?

Permit Application Rejected  
 Permit Opened  
 Permit Close Date Extended  
 Permit Closed


Confidential Page 39 4/7/2004  
Specified Technologies Inc. • 800-992-1180 • www.firestop.com

**NOT CONSIDERED A CLOSEOUT!**



# Firestop Installer Worksheet

- This document would be picked up and returned to the firestop office
- List all information of the installation
- A log of who, what, when and how
- Use as an inspection tool
- Accountability!





# Penetration Labels – Accountability?

- Product used
- Date of installation
- Contractor information
- UL System#

**WARNING!**  
**Firestopped Penetration**

This penetration has been sealed with Specified Technologies Inc. (STI) SpecSeal® Firestopping materials.

**DO NOT REMOVE!**

To maintain UL Classification in retrofitting, reseal with STI SpecSeal® Firestopping materials ONLY.

Product Installed \_\_\_\_\_  
Date of Installation \_\_\_\_\_  
Installing Contractor \_\_\_\_\_  
Contractor Phone ( ) \_\_\_\_\_  
UL System# \_\_\_\_\_

 **SpecSeal®**  
Firestop Products  
Specified Technologies Inc.  
Toll Free: 800-992-1180

21000-800-00



# Specialized Training

- Outline topics include:
  - Firestop fundamentals
  - Containment
  - Fire-rated construction
  - Firestop penetrations — proper products selection
  - Proper installations
  - High traffic/re-Enterable applications
  - UL® firestop system parameters and testing
  - Construction joints
  - Myths about firestop




## Firestop Instructional Training I and II




# Installing Firestop

Where does it go...



Wall penetrations , by contrast, almost always require a symmetrical installation, sealing both sides of the wall




Floor penetrations generally require only a seal from one side







# Through-Penetrations

- Are there combustibles?
- Is there need for movement?



# Composite Sheet For large Openings






# Specific Issues

## High Traffic Openings


- Cable penetrations are large percentage of Issues
- Infection control and acoustics?
- Fire barrier management over time is a significant challenge!

Long term sustainable designs are the key!






# Small Cable Applications



# Traditional Methods For HTO's


## Small Opening:

- Run sleeves through the wall or floor
- Firestop using sealant or putty




## Medium to Large Openings:

- Stop tray before wall and run multiple sleeves
- Run tray through opening and use pillows



# Maintenance Free Devices (Pre Diagnosed Materials)






# Where High Traffic Will Be An Issue Or Real Estate Is An Issue



## Future Proof The Building



# No Requirement To Open, Close or Plug






# Don't Just Take our Word for it

Issued by UL® Confirming Code Compliance of EZ-Path® to:




- International Building Code® (IBC)
- International Fire Code® (IFC)
- NFPA 101: Life Safety Code®
- IFC and LSC Include Requirements For Inspection And Maintenance Of Any Fire Protective Element In The Building.

*“The EZ-Path® Series 22, 33, and 44+ Fire-Rated Pathways do not require regular maintenance...” (UL ER14579-01 Section 6.1)*








# Floor Grid: Before and After






# More Cable In A Concentrated Area



# In Combination With Other Products





# Future Proof In The Design



# Cost Of Ownership

## Key Assumptions:

### Penetrations

Reset

Number of Penetrations (Computed based on EZ-Path Capacity)

100

### Devices



Device	# of Devices	Hours to Install	Re-Entry Hours
EZ-Path® 44+	100	0.5	0.5
Twist Sleeve	125	0.75	1.5
Steel Sleeve & Putty	200	1	2

### Labor

Labor Cost per Hour to Install/Re-Enter


\$ 90

Number of Re-Entries per Year

4

## Saving Advantages:

5 Year Life Cycle Cost of...



# Adjust The Numbers To Fit Your Project

## Labor

Labor Cost per Hour to Install/Re-Enter	\$ 90
Number of Re-Entries per Year	4
% Original Penetrations to Re-Enter	50%
Cost per Hour to Inspect	\$ 65
% Inspection Cost Allocated to Penetrations	25%
Allocated Cost per Hour to Inspect	\$ 16.25
% Penetrations to Inspect	100%





## ➔ Ongoing Inspection Cost per Year

### Cost of Inspections

Device	# of Devices	% Penetrations to Inspect	Labor Hours per Opening	Number of Sides to Inspect	Hourly Cost to Inspect	Annual Inspection Cost	5 Years	10 Years
EZ-Path® 44+	100	100%	0	0	\$16	\$0	\$0	\$0
Twist Sleeve	125	100%	1	1	\$16	\$2,031	\$10,156	\$20,313
Sleeve & Putty	200	100%	1	2	\$16	\$6,500	\$32,500	\$65,000

## ➔ Re-Entry Costs

### Cost of Re-Entry

Device	# of Devices	Re-entry Hours per Opening	Per Hour Labor Charge	Cost per Re-Entry	# Re-Entries per Year	% Original Penetrations Re-Entered	Annual Cost of Re-Entry	5 Years	10 Years
EZ-Path® 44+	100	0.5	\$90	\$45	4	50%	\$9,000	\$45,000	\$90,000
Twist Sleeve	125	1.5	\$90	\$135	4	50%	\$33,750	\$168,750	\$337,500
Sleeve & Putty	200	2	\$90	\$180	4	50%	\$72,000	\$360,000	\$720,000

# Bottom Line Cost Of Not Using EZ-Path!

## 5 Year Life-Cycle Cost

5 Year Life-Cycle Cost						EZ-Path® Advantage
Device	# of Devices	Initial Cost	Inspection	Re-Entry	Total	Life-Cycle Cost Savings
EZ-Path® 44+	100	\$43,000	N/A	\$45,000	\$88,000	-
Twist Sleeve	125	\$40,188	\$10,156.25	\$168,750	\$219,094	\$131,093.75
Sleeve & Putty	200	\$28,000	\$32,500.00	\$360,000	\$420,500	\$332,500.00


## Bottom Line

Here's what you'll save *per device* when you use EZ-Path® instead of:

(Per Device)	Five Years	Ten Years
Twist Sleeve	\$1,049	\$2,120
Sleeve & Putty	\$1,663	\$3,400


# You Can Take It Out To 10 Year Life Cycle Cost

10 Year Life-Cycle Cost						EZ-Path® Advantage
Device	# of Devices	Initial Cost	Inspection	Re-Entry	Total	Life-Cycle Cost Savings
EZ-Path® 44+	100	\$43,000	N/A	\$90,000	\$133,000	-
Twist Sleeve	125	\$40,188	\$20,312.50	\$337,500	\$398,000	\$265,000.00
Sleeve & Putty	200	\$28,000	\$65,000.00	\$720,000	\$813,000	\$680,000.00







# Over Filled Sleeves



# Clamp It For Compliance












# UL Burn Test (AFTER)




# Drop Ceiling Issues!





# Clean Cable Management Approach







# Clean Application For Tiles



## Cable Management



# Series 44 NEZ





# Containment Construction Joints





# Joint Applications

**SpecSeal**  
FIRESTOP PRODUCTS

# AS200

AS200 Elastomeric Spray




# TTG

SpeedFlex<sup>®</sup> TTG Track Top  
Gasket





**FIRESTOP**  
SPECIFIED TECHNOLOGIES INC.



# BIM & Clash Management

- Complete library of BIM objects & tools
- Free Firestop Clash Management plug in
  - Finds clash locations for firestop assemblies
  - Groups clashes with similar properties
  - Reduces amount of systems for project
  - Automatically performs STI System Search
  - Places UL® System at clash location
  - Provides openings reports of coordination







Streamline your  
firestop tracking  
process



ACCESS  STI







One simple tool to  
make your job easier

Plans start at \$29.99





Streamline your firestop tracking process today.

Cloud-Based Data  
Retrieval

Get started for free







Document, track, and inspect firestop items.

[Watch the video](#)

- ✓ Fully interactive floor drawings
- ✓ Use mobile devices (phone, tablet, web)


- ✓ 24 hour team member notifications
- ✓ Detailed reports including Corrective Action Reports





# FS Locator = Complete Documentation

- Use mobile tools (phone, tablet, web)
- Platforms include both iOS and Android
- All functions can be done on either app or web
- **Interactive with underlying floor drawings**
- Streamline the firestop tracking process
- Turn-key solution with pre-printed QR labels



iPhone 8 - 11.2



# This Is How You Win!

- Proactive approach  
(Barrier Management Program)
- Reduce costs by:  
(Standardization of Systems)
- UL systems that meet the requirement
- Deliver a long term “Sustainable” Facility



Set up an appointment to learn more:

[Kmason@stifirestop.com](mailto:Kmason@stifirestop.com)

810-650-3419

Specified Technologies Inc

800-992-1180

[www.stifirestop.com](http://www.stifirestop.com)

